

Datasheet Conveyor Belt



**NITTA CORPORATION
OF HOLLAND**

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
2 LRWAF 907 VB
- **Nitta Japan code:**



Construction: 2 plies polyester, rigid, antistatic

	TOP COVER	INNER LAYER	BOTTOM SIDE	
Material:	Felt	PVC	Whisper fabric	
Thickness:	2		-	mm (approx.)
Colour:	Black	Black	-	
Hardness:	-		-	
Profile:	-		-	

Total thickness: 3,6 **mm (approx.)**
Weight: 3 **kg/m² (approx.)**
Max. width: 2000 **mm**
Belt support: Sliderbed (Rollers), Flat

Rating at 1% elongation: 10 **N/mm**
Advised pretension: 4 - 7 **N/mm**
Maximum allowable tension: 18 **N/mm**
Temperature range: -10 **to** +80 **°C**

Minimum pulley diameters:
Flexing: 50 **mm**
Backflexing: 140 **mm**

Special approval: Not applicable

Applications: Luggage handling in airports and passenger terminals
 Internal transport, post offices and distribution centres
 Accumulation belt

Date of issue 22-07-2014-1

Your Partner In Belting Solutions

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nittacorporation.com